



CONCRETE BONDER & FORTIFIER

◆ The Pro's Choice Since 1936



Sakrete® Bonder & Fortifier is a latex copolymer that may be used as either a paint-on bonder (straight from the bottle) or as a fortifier/ admixture (mixed 1:1 with water).

Features:

- Improves bond strength to existing concrete
- Improves resistance to water penetration
- Increases adhesion, impact strength and abrasion resistance

Use For:

- In combination with cementitious concrete repair materials to improve bond of new concrete to old concrete

Yield/Coverage:

Container Size	Yield
1 qt (0.95 L)	125 - 200 ft ² (12 - 19 m ²)
1 gal (3.8 L)	500 - 800 ft ² (46 - 74 m ²)

NOTE: The yield is approximate and does not allow for waste and spillage.

Preparation:

Area to be resurfaced should be structurally sound. Clean the area thoroughly removing all dirt, oil, grease, paint and loose material, and any other foreign materials that will inhibit bond.

Mixing:

Mix entire contents thoroughly before using. Do not shake. Concrete Bonder & Fortifier can be used in two ways. Where improved resistance to water or chemical penetration or resistance to freeze/thaw damage are the primary concerns, use as a fortifier/admixture. Where improving bond strength is the main concern, use as a paint-on.

For use as a paint-on bonder:

1. Stir Bonder & Fortifier and apply with a paintbrush.
2. Cover the area completely to insure proper bond.
3. Bonder & Fortifier should be tacky to the touch during application of fresh patching material.
4. Apply the prepared patching material and trowel to a smooth finish. For best results mix a slurry consisting of 2 parts Bonder & Fortifier with one part portland cement.

5. Apply slurry with a paintbrush. Cover the area completely to insure proper bond.

NOTE: *Proper application and installation of all Sakrete products are the responsibility of the end user.*

Safety:

READ and UNDERSTAND the Safety Data Sheet (SDS) before using this product. WARNING: Wear protective clothing and equipment. For emergency information, call CHEMTREC at 800-424-9300 or 703-527-3887 (outside USA).

KEEP OUT OF REACH OF CHILDREN.

Limited Product Warranty:

The manufacturer warrants that this product shall be of merchantable quality when used or applied in accordance with the manufacturer's instructions. This product is not warranted as suitable for any purpose other than the general purpose for which it is intended. This warranty runs for one (1) year from the dates the product is purchased. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS LIMITED TO THE DURATION OF THIS WARRANTY. Liability under this warranty is limited to replacement or defective products or, at the manufacturer's option, refund of the purchase price. CONSEQUENTIAL AND INCIDENTAL DAMAGES ARE NOT RECOVERABLE UNDER THIS WARRANTY.