

# Product Information

## MATTE FINISH SEALER

### Description

Tile Star Matte Finish Sealer is a water based coating designed for use on quarry tile and other masonry surfaces where a matte or no-gloss finish is desired and where the preservation of the integrity of the tile is a consideration.

This product represents a true breakthrough in polymer technology. It provides a tough, durable, protective finish, while maintaining the desirable natural, low gloss appearance characteristic of quarry, slate, porcelain and other unglazed tiles.

Tile Star Matte Finish Sealer has a very low odor, is easy to apply, dries quickly, is nonflammable, recoatable and long wearing.

### Recommended Uses

Matte Finish Sealer can be applied to quarry tile, porcelain, terrazzo, slate, concrete and other masonry type surfaces. Equally effective for residential and commercial use. This product can also be used for sealing only grout lines. It affords excellent protection and will not change the look of the grout.

### WARNING: WET FLOORS ARE SLIPPERY.

Use proper caution anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

### Directions

**NEW INSTALLATIONS:** Floors installed with thin set mortar must be allowed to cure for four weeks after grouting before they can be sealed. Floors installed with epoxy grout must be allowed to cure for 72 hours after grouting.

**PREPARATION:** Clean floor thoroughly to remove all surface soil and stains. Any existing seals must be removed with an appropriate stripper. Rinse well with clean water and allow floor to air dry or wet vac.

**APPLICATION:** Pour a small amount of sealer onto the floor and carefully spread it into a very thin film using a clean cotton string mop. Take care to use even, overlapping strokes and not to allow any excess sealer to build up in grout lines. Do small areas at a time. A second coat may be applied after the first coat has been dry for 30 minutes.

**MAINTENANCE:** Clean floor as needed using Tile Star Neutral Cleaner.

**RECOAT:** Additional thin coats may be applied to clean, dry floors. However, gloss may start to build up if too many coats are present. When this occurs, strip floor and start over with two fresh coats.

**CAUTION:** Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally.

**FIRST AID:** In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN

### Specifications

Type product .....	Masonry sealer/finish
pH .....	8.5 ± 0.3
Appearance .....	Opaque white
Percent solids .....	18
Weight per gallon .....	8.58 lbs.
Freeze/thaw stability .....	Passes 3 cycles
Flash point .....	None
Coverage .....	1600 - 2000 sq. ft. per gallon