Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER		
Product Name:	1.	ProSpec Permaflex 300 Product Code: Gray - 65250311 (50lb) White - 65467516 (50lb)
	2.	ProSpec Permaflex 400 Product Code: Gray - 65252890 (50lb) White - 65252900 (50lb)
	3.	ProSpec Permaflex 600 Product Code: Gray - 65304760 (50lb), 65467550 (25lb) White - 65304785 (50lb), 65467551 (25lb)
	4.	ProSpec Permalastic Product Code: Gray - 65465001 (50lb) White - 65465002 (50lb)
	5.	ProSpec Permaset 275 Product Code: Gray - 65467505 (50lb) White - 65467506 (50lb)
	6.	ProSpec Permaset 200 Product Code: Gray - 65467505 (50lb) White - 65467506 (50lb)
	7.	ProSpec Medium Bed Permaflex 300 Product Code: Gray – 653000479 (50lb) White – 65300481 (50lb)
	8.	ProSpec Medium Bed Permaset 275 Product Code: Gray – 65462332 (50lb) White – 65462330 (50lb)
1.2 RECOMMENDED USE OF CH	EMICA	AL AND RESTRICTIONS ON USE
Use:	Vario	DUS.
1.3 DETAILS OF THE SUPPLIER	OF TH	E SAFETY DATA SHEET
Name/Address:	8201	sal American, Inc. Arrowridge Blvd. lotte, NC 73
Telephone Number:	800-3	334-0784 Tech Service 8:00 to 5:00 Eastern, MonFri.
1.4 EMERGENCY TELEPHONE N	UMBE	R
Emergency Telephone Number:		MTREC 800-424-9300 ERNATIONAL + 01-703-527-3887
Date of Preparation:	Febr	uary 1, 2013 Version #: 1.1

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200

Page 1 of 12

Print date: 2013-02-01

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

Acute toxicity 4 (Oral) Skin irritation 2 Serious eye damage 1 Skin sensitization 1 Carcinogenicity 1A Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS

Hazard Pictogram:	
Signal Word:	Danger
Hazard Statement:	Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure.
Prevention:	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust.
Response:	If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.2 ADDITIONAL INFORMATION	

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified:

Not applicable.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 2 of 12

ProSpec Permaflex 300: 33.2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Permaflex 400: 33.6 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Permaflex 600: 37.7 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Permalastic: 31.3 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Permaset 275: 31.3 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Permaset 200: 29.8 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Medium Bed Permaflex 300: 33.6 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProSpec Medium Bed Permaset 275: 31.9 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	UN #	H / F/ R / *	CAS No	Wt. %
Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	40 - 70
Portland cement	Not available.	1/0/0	65997-15-1	15 - 40
				1 – 5;
Calcium carbonate	Not available.	1/0/0	1317-65-3	5 – 10**
Ferric oxide	UN1376	1/0/0	1309-37-1	3 - 7
Gypsum	UN3077	Not available.	13397-24-5	1 - 5
Magnesium oxide	UN1418	2/0/0	1309-48-4	1 - 5
Calcium oxide	UN1910	3/0/1	1305-78-8	1 - 5

The exact percentage (concentration) of chemicals has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

** ProSpec Permaset 200 contains 1 – 5% Calcium Carbonate. All other products listed in Section 1 contain 5 – 10% Calcium Carbonate.

* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye:In case of contact, immediately flush eyes with plenty of water for at
least 15 minutes. If easy to do, remove contact lenses, if worn. Get
medical attention immediately.Skin:In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes. Wash clothing before
reuse. Call a physician if irritation develops and persists.Inhalation:If breathing is difficult, remove victim to fresh air and keep at rest in a
position comfortable for breathing. Get medical advice/attention if
you feel unwell.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 3 of 12

Ingestion:	If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.
4.2 MOST IMPORTANT SYMPT	OMS AND EFFECTS, BOTH ACUTE AND DELAYED
Eye:	Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Skin:	Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
Inhalation:	May cause respiratory tract irritation.
Ingestion:	Harmful if swallowed. May cause stomach distress, nausea or vomiting.
4.3 INDICATION OF ANY IMME	DIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED
Note to Physicians:	Symptoms may not appear immediately.

Note to Physicians:	Symptoms may not appear immediately.
Specific Treatments:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability:

Not flammable by WHMIS/OSHA criteria.

5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200

Page 4 of 12

Print date: 2013-02-01

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment:	Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for Cleaning-Up:	Vacuum or sweep material and place in a disposal container.
	Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling:	Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8)
General Hygiene Advice:	Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2 CONDITIONS FOR SAFE S	TORAGE, INCLUDING ANY INCOMPATIBILITIES
Storage:	Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

sprinklers. (See section 10)

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits					
Ingredient	OSHA-PEL	ACGIH-TLV			
	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp))				
Silica, crystalline,	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total))				
quartz	((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m³			
		1 mg/m ³ (no asbestos and <1%			
Portland cement	15 mg/m ³ (total); 5 mg/m ³ (resp)	crystalline silica, respirable fraction)			
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³			
Ferric oxide	10 mg/m ³	5 mg/m ³ (iron oxide fume; dust as Fe)			
	15 mg/m ³ TWA (total dust)				
Gypsum	5 mg/m ³ TWA (respirable fraction)	10 mg/m ³			
Magnesium oxide	15 mg/m ³	10 mg/m ³			
Calcium oxide	5 mg/m³	2 mg/m ³			

8.2 EXPOSURE CONTROLS

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASSURES

Personal Protective Equipment:

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 5 of 12

ProSpec[®]

SAFETY DATA SHEET

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin Protection:

Hand Protection: Wear suitable waterproof gloves.

Body Protection: Wear suitable waterproof protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	Not available.
Odor:	Not available.
Odor Threshold:	Not available.
Physical State:	Powder.
pH:	12 - 13
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not Flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density/Specific Gravity:	Not available.
Solubility:	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 6 of 12

Percent Volatile, wt. %:

VOC content, wt. %:

Not available.

0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Incompatible materials. Moisture.

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

- **Eye:** Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- **Skin:** Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
- Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
- Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
Silica, crystalline,	Ca [25 mg/m ³ (cristobalite, tridymite); 50 mg/m ³ (quartz, tripoli)]	Not available.	Oral 500 mg/kg, rat
quartz Portland cement	5000 mg/m ³	Not available.	Not available.
Calcium carbonate	Not available.	Not available.	Not available.
Ferric oxide	2500 mg Fe/m ³	Not available.	Oral >10000 mg/kg, rat
Gypsum	Not available.	Not available.	Not available.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 7 of 12

Print date: 2013-02-01

Magnesium oxide	75	50 mg/m ³	Not avai	ahle	Oral >5000 mg/kg, rat
Calcium oxide		5 mg/m^3	Not avai		Oral 500 mg/kg, rat
		d overall Chemical A	cute Toxici	tv Valu	
LC50 (inhalati		LD50 (oral)		ty valu	LD50 (dermal)
Not available		500 – 620 mg/kg			Not available.
		500 – 020 mg/kg	<i>.</i>		
Ingredient				Poter	sted as Carcinogen or ntial Carcinogen OSHA, ACGIH, CP65)*
Silica, crystalline, qua	artz			G-A2	, I-1, N-1, CP65
Portland cement				07.2	G-A4
Calcium carbonate					Not listed.
Ferric oxide					G-A4, I-3
Gypsum Magnapium avida					Not listed. G-A4
Magnesium oxide Calcium oxide					Not listed.
		CHRONIC EFFECTS	JF SHOR I-		ONG-TERM EXPOSURE
Skin Corrosion/Irritat	tion:	Causes skin irritatio moisture.	n. May cau	se burn	s in the presence of
Serious Eye Damage	/Irritation:	Causes serious eye moisture.	damage. Ma	ay caus	e burns in the presence of
Respiratory Sensitiza	ation:	Based on available	data, the cl	assifica	tion criteria are not met.
Skin Sensitization:		May cause an allergi	c skin react	ion.	
STOT-Single Exposu	re:	May cause respirate	ory irritation		
Chronic Health Effec	ts:	from occupational s for Research on Ca Program (NTP) as a respirable crystalling lung disease, which factor of individual s respirable silica dus severity of the disea	ources is lis ncer (IARC a lung carcin e silica has may be dis susceptibility t, the risk o use is clearl	sted by nogen. been ki sabling. y to a gi f contra y relate	Prolonged exposure to nown to cause silicosis, a While there may be a
Carci	inogenicity:	May cause cancer.			
Germ Cell M	utagenicity:	This product is not o	classified as	s a muta	agen.
Reproductive Toxicit	y:				
Deve	elopmental:	Based on available	data, the cl	assifica	tion criteria are not met.
	Teratogen	icity: Not hazardou	s by WHMI	S/OSH	A criteria.
	•	icity: Not hazardou	•		
	Fertility:	-	•		tion criteria are not met.
STOT-Repeated Expo	•	Causes damage to exposure.			
Name: ProSpec Permaflex 30 ProSpec Permaflex 40 ProSpec Permaflex 60 ProSpec Permalastic ProSpec Permaset 27	00 00		Page 8 of 12		Print date: 2013-02

ProSpec Permatlex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200

Trade

Aspiration Hazard:	Based on available data, the class	ification criteria are not met.	
Toxicologically Synergistic Materials:	Not available.		
Other Information:	Not available.		
Se	ction 12: ECOLOGICAL INFORMATIO	N	
12.1 ECOTOXICITY			
Acute/Chronic Toxicity:	No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.		
12.2 PERSISTENCE AND DEGRA	ADABILITY		
Not available.			
12.3 BIOACCUMULATIVE POTER	NTIAL		
Bioaccumulation:	Not available.		
12.4 MOBILITY IN SOIL			
Not available.			
12.5 OTHER ADVERSE EFFECTS	5		
Not available.			
Sec	ction 13: DISPOSAL CONSIDERATION	IS	
13.1 WASTE TREATMENT METH	IODS		
Disposal Method:	This material must be disp	osed of in accordance with all	
Other disposal recommendatio	local, state, provincial, and		
-	local, state, provincial, and	federal regulations.	
Se	ns: Not available.	federal regulations.	
14.1 UN NUMBER	local, state, provincial, and ns: Not available.	I federal regulations.	
14.1 UN NUMBER DOT	local, state, provincial, and ns: Not available. ection 14: TRANSPORT INFORMATION TDG	d federal regulations.	
14.1 UN NUMBER DOT Not regulated.	Iocal, state, provincial, and ns: Not available. ection 14: TRANSPORT INFORMATION TDG Not regulated.	l federal regulations.	
14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated.	d federal regulations. N NOM-004-SCT2-1994 Not regulated.	
14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM DOT	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG	Nom-004-SCT2-1994 Not regulated.	
14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM DOT Not applicable.	Iocal, state, provincial, and ns: Not available. ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable.	d federal regulations. N NOM-004-SCT2-1994 Not regulated.	
Set 14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAME DOT Not applicable. 14.3 TRANSPORT HAZARD CLA	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable. SS (ES)	NOM-004-SCT2-1994 Not regulated. NOM-004-SCT2-1994 Not applicable.	
Se 14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM DOT Not applicable. 14.3 TRANSPORT HAZARD CLA DOT	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable. SS (ES) TDG	NOM-004-SCT2-1994 Not regulated. NOM-004-SCT2-1994 Not applicable. NOM-004-SCT2-1994	
Set 14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAME DOT Not applicable. 14.3 TRANSPORT HAZARD CLA DOT Not applicable. Not applicable.	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable. SS (ES)	Nom-004-SCT2-1994 Not regulated. Not applicable.	
Se 14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM DOT Not applicable. 14.3 TRANSPORT HAZARD CLA DOT	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable. SS (ES) TDG	NOM-004-SCT2-1994 Not regulated. NOM-004-SCT2-1994 Not applicable. NOM-004-SCT2-1994 Not applicable.	
Se 14.1 UN NUMBER DOT Not regulated. 14.2 UN PROPER SHIPPING NAM DOT Not applicable. 14.3 TRANSPORT HAZARD CLA DOT Not applicable. 14.4 PACKING GROUP	Iocal, state, provincial, and ns: Not available. Ection 14: TRANSPORT INFORMATION TDG Not regulated. ME TDG Not applicable. SS (ES) TDG Not applicable.	NOM-004-SCT2-1994 Not regulated. NOM-004-SCT2-1994 Not applicable. NOM-004-SCT2-1994	

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Ferric oxide	Not listed.	Not listed.	Not listed.	Not listed.
Gypsum	Not listed.	Not listed.	Not listed.	Not listed.
Magnesium oxide	Not listed.	Not listed.	Not listed.	Not listed.
Calcium oxide	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
Portland cement	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Ferric oxide	DSL	Yes.
Gypsum	DSL	No.
Magnesium oxide	DSL	Yes.
Calcium oxide	DSL	Yes.

Trade Name: ProSpec Permaflex 300 & MB 300 ProSpec Permaflex 400 ProSpec Permaflex 600 ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 Page 10 of 12

NFPA - Na	tional Fire Protection Association:
Health:	3
Fire:	1
Reactivity:	0
HMIS - Hazar	dous Materials Identification System
Health:	3*
Fire:	1
Reactivity:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme


WHMIS Classification(s):

Class D2A – Carcinogenicity Class D2A - Chronic Toxic Effects Class E - Corrosive Material

WHMIS Hazard Symbols:



Mexico Classification:



Blue = Health	Red = Flammability	Yellow = Reactivity	White = Special	
Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme				
SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:				
CP65 California Proposition 65 OSHA (O) Occupational Safety and Health Administration.				
ACGIH (G)	American Conference of A1 - Confirmed human carcin A2 - Suspected human carcin A3 - Animal carcinogen. A4 - Not classifiable as a hum A5 - Not suspected as a hum	nogen. nan carcinogen.	ial Hygienists.	
1 - The agent (mixture) is 2A - The agent (mixture) humans and sufficient ev 2B - The agent (mixture) humans in the absence 3 - The agent (mixture, e		or Research on Cancer. cinogenic to humans. obably carcinogenic to humans ce of carcinogenicity in experin possibly carcinogenic to humans ficient evidence of carcinogeni ure circumstance) is not classi ure circumstance) is probably	nental animals. ; there is limited evidenc city in experimental anin fiable as to its carcinoge	ce of carcinogenicity in nals. enicity to humans.
Trade Name: ProSpec Per ProSpec Per ProSpec Per ProSpec Per	rmaflex 400 rmaflex 600	Page 11	of 12	Print date: 2013-02

ProSpec Permalastic ProSpec Permaset 275 & MB 275 ProSpec Permaset 200 2013-02-01

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation:	February 1, 2013
Expiry Date:	February 1, 2016
Version:	1.1
Revision Date:	February 1, 2013

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by:	Nexreg Compliance In Phone: (519) 488-512 <u>www.nexreg.com</u>	
Prepared for:	Bonsal American, Inc.	

End of Safety Data Sheet